



ADVANTAGES

- Zero tempering
- Zero Emission
- Zero Outgasing
- ProSafe + REACH compliance
- H13 in all Temp. ranges $\geq 99,95\%$ at MPPS with DEHS
- Temperature resistant up to 350°C
- Patented construction

Application	HEPA filter protection for clean processes at high temperature, especially for Life Science (depyrogenation tunnels, ovens)
Type	High temperature HEPA filter
Frame	Stainless steel
Media	Glass fiber
Separator	Stainless steel
Sealant	Inorganic polymer
Max. final pressure drop	700Pa
Comment	Temperature: up to 350 °C with peaks up to 400 °C Remarks: ISO 5 under all production steps. Please note installation and assembly instructions! Other editions on request (with gasket, or sizes)



Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
DHT14-762x610x292-0-SP	H14	762x610x292	1675/190	44,0
DHT13-762x610x292-0-SP	H13	762x610x292	2250/250	44,0
DHT14-610x610x292-0-SP	H14	610x610x292	1340/190	26,0
DHT13-610x610x292-0-SP	H13	610x610x292	1850/250	26,0
DHT14-457x610x292-0-SP	H14	457x610x292	1000/190	19,5
DHT13-457x610x292-0-SP	H13	457x610x292	1310/250	19,5
DHT14-305x610x292-0-SP	H14	305x610x292	670/190	13,0
DHT13-305x610x292-0-SP	H13	305x610x292	840/250	13,0
DHT14-762x610x150-0-SP	H14	762x610x150	1040/190	34,0
DHT13-762x610x150-0-SP	H13	762x610x150	1260/250	34,0
DHT14-610x610x150-0-SP	H14	610x610x150	840/190	16,0
DHT13-610x610x150-0-SP	H13	610x610x150	990/250	16,0
DHT14-457x610x150-0-SP	H14	457x610x150	610/190	12,0
DHT13-457x610x150-0-SP	H13	457x610x150	690/250	12,0
DHT14-457x457x150-0-SP	H14	457x457x150	450/190	9,0
DHT13-457x457x150-0-SP	H13	457x457x150	510/250	9,0
DHT14-305x610x150-0-SP	H14	305x610x150	420/190	8,0
DHT13-305x610x150-0-SP	H13	305x610x150	460/250	8,0

Pressure drop: $\pm 10\%$

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-22