



ADVANTAGES

- Low outgassing components
- High media cleanliness
- Predicted removal efficiency and lifetime by Camfil's proprietary software
- Typical target gases: VOCs, acids, bases, ozone
- Customizable dimensions and media configuration
- Individually VOC outgassing tested
- Wide range of dimensions



Application	Adaptor frames are available for installation above fan filter units, mini-environment or process equipment
Frame	Anodized aluminium
Gasket	Polyurethane;EPDM
Media	Activated Carbon;Impregnated Activated Carbon
Max Temperature (°C)	40
Relative Humidity max	30% - 70%
Particle cleanliness	ISO Class 6
Comment	Knife position: KD - downstream, KU - upstream Gasket Position: 01 - downstream, 10 - upstream Faceguard Position: 20 - downstream, 02 - upstream, 22 - Both downstream and upstream Available filter depth without knife edge: 66, 90, 110, 150, 172, 200, and 213 mm Available filter depth with knife edge: 66 (+38), 90 (+38), 110 (+38), 150 (+15) mm Outgassing: Individually outgassing tested for VOC emissions

Type	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
NXPP B	610x610x90	535/15	5
NXPP B	1220x610x90	1070/15	10
NXPP A	610x610x90	535/15	5
NXPP A	1220x610x90	1070/15	10
NXPP V	610x610x90	535/15	5
NXPP V	1220x610x90	1070/15	10
NXPP ABV	610x610x150	535/50	14
NXPP ABV	1220x610x150	1070/50	28

Other dimensions and media combinations available on request. Adapter frames for FFU installation available on request