



ADVANTAGES

- Self-cleaning air filter cartridges
- Improved air distribution
- Suitable also in high humidity conditions
- Suitable as prefilter for filter class E10, E12
- Increased air to cloth ratio thanks to Hemi-Pleat™ technology.
- Patented HemiPleat™ technology-proven open
- Water repellent media protected by metal liners
- Each filter set is shipped together in one carton
- Galvanized metal finish

Application	For desert/dry/ heavy dust load areas
Frame	Galvanized steel;Stainless steel
Gasket	Polyurethane, endless foamed;EPDM
Media	Synthetic
Separator	Hot-melt
Sealant	Polyurethane
Rec. final pressure drop	1000 Pa
Max Temperature (°C)	70° C
Relative Humidity max	100%
Pleat	HemiPleat
Comment	Additional information: Available as dimple pleated and in fire retardant version on request.

Camfil CamPulse with proven HemiPleat™ technology, combined with a synthetic media, delivers valuable benefits to gas turbine operation and maintenance.

Type	EN779	Length (mm)	Diameter (mm)	Length 2 (mm)	Diameter 2 (mm)	Airflow/pressure drop (m³/h/Pa)	Area (m²)	Weight (kg)	ASHRAE 52.2-2017
CamPulse Cyl/Cyl	F7	660	445	660	324	2500/140	34.7	12.8	MERV 16
CamPulse Co/Cyl	F7	660	445/324	660	324	2500/165	34,7	12,8	
Tenkay 34"	F7	864	324			1150/147			

CyCy = Large Cylindrical, Small cylindrical
CoCy= Large Conical, Small Cylindrical