



## ADVANTAGES

- Large dust holding capacity
- Suitable for variable airflow
- Fine fibre ensures that filter maintains its efficiency throughout its life in the system
- Robust design

<b>Application</b>	Built-up banks, rooftops, split systems, free-standing units, package systems and air handlers
<b>Frame</b>	Galvanised steel
<b>Gasket</b>	Neoprene
<b>Media</b>	Glass fiber
<b>Rec. final pressure drop</b>	450 Pa
<b>Max Temperature (°C)</b>	70°C
<b>Comment</b>	UL 900 Microfine glass media formed into full pack depth pleats separated by corrugated aluminum separators



Art. No.	Type	EN779	ASHRAE 52.2-2017	ISO16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
2150002	3CPM-242412-60	M6	MERV 11	ePM10 70%	610x610x292	3400/75	8.6
2155001	3CPM-65-242412	M6	MERV 11	ePM10 70%	592x592x292	3400/110	8.6
2150001	3CPM-122412-60	M6	MERV 11	ePM10 70%	305x610x292	1700/75	6.4
2155002	3CPM-65-241212	M6	MERV 11	ePM10 70%	287x592x292	1700/110	6.4
2151007	3CPM-242412-90	F7	MERV 13	ePM1 55%	610x610x292	3400/110	8.6
2156001	3CPM-85-242412	F7	MERV 13	ePM1 55%	592x592x292	3400/145	8.6
2151008	3CPM-122412-90	F7	MERV 13	ePM1 55%	305x610x292	1700/110	6.4
2156002	3CPM-85-241212	F7	MERV 13	ePM1 55%	287x592x292	1700/145	6.4
2152003	3CPM-242412-95	F8	MERV 14	ePM1 70%	610x610x292	3400/135	8.6
2157003	3CPM-95-242412	F8	MERV 14	ePM1 70%	592x592x292	3400/160	8.6
2152004	3CPM-122412-95	F8	MERV 14	ePM1 70%	305x610x292	1700/135	6.4
2157002	3CPM-95-241212	F8	MERV 14	ePM1 70%	287x592x292	1700/160	6.4