## **CAMPULSE GT POLYTECH HE**









## **ADVANTAGES**

- Better pulsability due to surface loading media technology
- Good pulsability
- Recommended as a pre-filter, not recommended as a final filter
- Self-cleaning cartridge filter with longer filter life and lower initial pressure drop
- Extends final filter life when used as a pre-filter

Application	For desert/dry/ heavy dust load areas
Frame	Galvanised steel;Stainless steel
Gasket	Polyurethane, endless foamed;EPDM
Media	Synthetic
Separator	Hot-melt
Sealant	Polyurethane
Rec. final pressure drop	1000 Pa
Max Temperature (°C)	70° C
Relative Humidity max	100%
Pleat	HemiPleat
Comment	Additional information: Available as dimple pleated and in fire retardant version on request.

Camfil CamPulse with proven HemiPleat™ technology, combined with a synthetic media, delivers valuable benefits to gas turbine operation and maintenance.

Type	EN779	ASHRAE 52.2-2017	Length (mm)	Diameter (mm)	Length 2 (mm)	Diameter 2 (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
CamPulse Cyl/Cyl	F7	MERV 16	660	445	660	324	2500/140	12.8
СоСу	F7	MERV 16	660	324	660	445	2500/195	12.8
Tenkay 34"	F7		864	324			1150/147	

CyCy = Large Cylindrical, Small cylindrical CoCy= Large Conical, Small Cylindrical

<sup>\*</sup>Turbomachinery ISO 29461-1 test standard is available upon customer request