



ADVANTAGES

- Galvanized filter frame
- 100% leakfree, individually scan tested
- High airflow (2,5 m/s)
- Scanable flat media pack surface

| | |
|---------------------------------|--|
| Application | HEPA-filter for high air flows |
| Gasket | Polyurethane, endless foamed |
| Media | Glass fiber |
| Separator | Hot-melt |
| Sealant | Polyurethane |
| Rec. final pressure drop | 1000 Pa |
| Max airflow | Nominal flow rate (if not, efficiency drops) |
| Max Temperature (°C) | 70°C |
| Relative Humidity max | 100% |
| Comment | Fire rating: DIN 53438 Class Fl |



| Art. No. | Type | EN1822 | Dimensions WxHxD (mm) | Airflow/pressure drop (m ³ /h/Pa) | Weight (kg) |
|----------|-----------------------|--------|-----------------------|--|-------------|
| 1408031 | DE13-305x610x292-P0-S | H13 | 305x610x292 | 1500/250 | 13 |
| 1408032 | DE13-610x610x292-P0-S | H13 | 610x610x292 | 3400/250 | 16 |
| 1408033 | DE13-762x610x292-P0-S | H13 | 762x610x292 | 3750/250 | 20 |
| 1408034 | DE14-305x610x292-P0-S | H14 | 305x610x292 | 1500/290 | 13 |
| 1408035 | DE14-610x610x292-P0-S | H14 | 610x610x292 | 3400/290 | 16 |
| 1408036 | DE14-762x610x292-P0-S | H14 | 762x610x292 | 3750/290 | 20 |

Frame is available in Electro zinc

*Other sizes are available on request