



ADVANTAGES

- 100% incinerable
- Can be used to upgrade existing installations
- Lightweight and clean
- “2 in 1” filtration solution; particulate and molecular.
- Rapid Adsorption Dynamics (RAD)
- Ozone rating Oz5 or Oz6

Application	High efficiency particle filtration for deodarisation and removal of gas pollutants, used for filtration in offices, airports
Type	Pleated Panel
Frame	Water resistant cardboard
Media	Synthetic/Activated Carbon
Dimensions	Filter front dimensions according EN 15805
Max airflow	1,25 x nominal flow
Temperature max	40° C
RH. max	30% - 70%
Installation Options	Front and side access housings and frames are available



Art. No.	Model Name	Note	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
5103010	CityPleat-480-594x594x95	CityPleat-480-594x594x95	G4	Coarse 65%	594x594x95	3185/50	3,8
5103011	CityPleat-200-594x594x95	CityPleat-200-594x594x95	G4	Coarse 65%	594x594x95	3185/90	2
5103009	CityPleat-480-289x594x95	CityPleat-480-289x594x95	G4	Coarse 65%	289x594x95	1500/50	1
5103008	CityPleat-200-289x594x95	CityPleat-200-289x594x95	G4	Coarse 65%	289x594x95	1500/90	1,9
5103001	CityPleat-100-594x594x44	CityPleat-100-594x594x44	G4	Coarse 65%	594x594x44	1900/135	1
5103005	CityPleat-200-594x594x44	CityPleat-200-594x594x44	G4	Coarse 65%	594x594x44	3175/135	1,8
5103004	CityPleat-200-289x594x44	CityPleat-200-289x594x44	G4	Coarse 65%	289x594x44	1500/135	0,9
5103007	CityPleat-100-289x594x44	CityPleat-100-289x594x44	G4	Coarse 65%	289x594x44	900/135	0,5

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-11-16

