CAMPGT









ADVANTAGES

- Reduces fuel/energy consumption
- Light weight construction for easy mounting
- Downstream synthetic scrim protection
- Fully incinerable

- F7 to E10 (EN779:2012 / En1822)
- ISO ePM1 70%, 85% and 95%
- Low pressure drop maximizes equipment output

Application	Suitable for demanding operating conditions like heavy polluted rural or industrial areas
Frame	Plastic moulded;ABS
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt Separator Technology
Sealant	Polyurethane
Grille, Downstream	Support grid for filtermedia
Rec. final pressure drop	450 Pa
Max Temperature (°C)	70°C
Relative Humidity max	100%
Comment	Additional information: 4 side PU sealant with scrim on 8 pack and 4 side sealant with 2 side scrim also available.

The CamPGT is an energy efficient solution functioning as a high efficiency filter in Camfil medium velocity multistage inlet houses. It is intended for inland industrial and rural areas. Its unique geometry provides a large inlet area and optimized air flow, thus offering a lower pressure drop than industry standard for V-shaped barrier filters.

Art. No.	Туре	EN779 EN1822	ASHRAE 52.2- 2017	ISO16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)	ePM1 e	PM1min	ePM2,5 e	PM2,5min	ePM10
PGT02011112210MY CamP	GT 4H-300, T	7 F7	MERV 14	ePM1 55%	592x592x292	4250/94	4,3	56	56	66	66	87
PGT02021112210MY CamP	GT 4H-300, T	8 F8	MERV 15	ePM1 70%	592x592x292	4250/110	4,3	72	72	80	80	92
PGT02031112210MY CamP	GT 4H-300, T	9 F9	MERV 16	ePM1 85%	592x592x292	4250/125	4,3	83	83	87	87	95
PGT02041112210MY Cam	PGT 4H-300, T10	E10			592x592x292	4250/200	4,3					

XL versions available on demand

^{*}Turbomachinery ISO 29461-1 test standard is available upon customer request