



ADVANTAGES

- Robust metal header frame
- Unique pocket design
- Available in a range of efficiencies
- Multi-pocket bag filter
- Comprehensive range of standard sizes

Application	Air conditioning applications
Type	Bag Filter
Frame	Galvanised steel
Media	Synthetic
Rec. final pressure drop	450
Temperature max	70
Installation Options	Holding frames: Front and side access housings and frames are available, Type 8 and FC Housings
Comment	Recommended final pressure drop: 450 Pa (suggested economical change point 250 Pa) Fire rating: UL 900



Art. No.	Model Name	Type	ASHRAE 52.2-2017	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Bags	Weight (kg)
3300065	A8	A8	MERV 14	ePM10 85%	592x592x600	3400/145	6	2.4
3300073	A5	A5	MERV 10	ePM10 60%	592x592x600	3400/75	6	2.4
3300041	A7	A7	MERV 13	ePM10 80%	592x592x600	3400/110	6	2.4
3300017	A6	A6	MERV 11	ePM10 70%	592x592x600	3400/100	6	2.4
3300066	B8	B8	MERV 14	ePM10 85%	490x592x600	2800/145	5	2.0
3300042	B7	B7	MERV 13	ePM10 80%	490x592x600	2800/110	5	2
3300018	B6	B6	MERV 11	ePM10 70%	490x592x600	2800/100	5	2
3300074	B5	B5	MERV 10	ePM10 60%	490x592x600	2700/75	5	2
3300067	C8	C8	MERV 14	ePM10 85%	287x592x600	1700/145	3	1.5
3300019	C6	C6	MERV 11	ePM10 70%	287x592x600	1700/100	3	1.5
3300075	C5	C5	MERV 10	ePM10 60%	287x592x600	1700/75	3	1.5
3300043	C7	C7	MERV 13	ePM10 80%	287x592x600	1700/110	3	1.5

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-10-10

