## CLEANSEAL EXTRACT EXHAUST/RETURN AIR HOUSING





## **ADVANTAGES**

- High corrosion protection againts decontamination agents
- Ensure localized control of potent compounds, eliminating the contamination of downstream ductworks
- Easily operation with scanning system for filter integrity test
- Tool-less filter clamping 100% secured and immediate
- Quick grid locking for immediate access to filter
- Long lasting reliability and tightness : robust fully welded construction

Application	CleanSeal Extract is wall mount equipment used for exhaust/return air system: Pharmaceutical, Biotechnology, Chemistry, Hospitals, and animal facilities.
Comment	Type: Fully welded Wall mount housing. Construction: Carbon steel, fully welded seams, accessories in Stainless Steel Finish: 3 Steps - white epoxy coated RAL 9010, qualified for high corrosion protection against decontamination agents Filter Seal: Endless PU gasket on filter. Connection: Rectangular pre-drilled flanges. Pressure Gauge: Pressure gauge is pre-installed on the equipment. Performance: The whole equipment could bear ±1000Pa.The overall leakage rate should no more than 0.25% per hour under 1000Pa pressure. Scanning system: Accourding to standard IS014644-3.

Art. No.	Туре	Dimensions WxHxD (mm)	Filter size HxWxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
WM10000C	CLE-SW-6P6-P-MD-SR6008-N-LS-AOOO	800x998x526	610x610x66		55
WM10001C	CLE-SW-6P6-P-MX-SR6008-N-LS-AOOO	800x998x526	610x610x90		55
WM10002C	CLE-SW-6P6-P-MG-SR6008-N-LS-AOOO	800x998x526	610x610x110		55
WM10003C	CLE-SW-6P6-P-48MD-SR6008-N-LS-AOOO	800x998x526	610x610x66		55
WM10004C	CLE-SW-6P6-P-NF-SR6008-N-LS-AOOO	800x998x526			55
15042392C	Megalam MDA-610x610-01/22	610x610x66	610x610x66	1000/250	4
15056166C	Megalam MXA-610x610-01/22	610x610x90	610x610x90	1500/250	5.6
15066022C	Megalam MGA-610x610-01/22	610x610x110	610x610x110	1800/250	5.3

<sup>\*</sup>Other model please contact Camfil Kunshan factory.