



ADVANTAGES

- 康斐爾專用軟件模擬去除效率以及壽命
- 典型去除氣體：揮發性有機物，酸，鹼，臭氧
- 低釋氣
- 介質潔淨度高

Application	潔淨室回風, 送風系統
Frame	不銹鋼; 鍍鋅鋼
Gasket	Polyurethane; EPDM
Media	活性炭; 浸漬活性炭
Sealant	Polyurethane
Rec. final pressure drop	Not a particulate filter. Molecular filters' initial pressure drop equals their final pressure drop. Consult with factory on end-of-life analysis.
最高溫度 (°C)	40°C
Relative Humidity max	30% - 70%
Particle cleanliness	ISO Class 6
Comment	密封墊位置: 01-下游, 10-上游 每片濾網出廠前都通過VOC測試



Type	Target contaminant	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
NXDP B	Bases	592x592x292	3300/50	15
NXDP B	Bases	287x592x292	1600/50	10
NXDP A	Acids	592x592x292	3300/50	15
NXDP A	Acids	287x592x292	1600/50	10
NXDP V	Organics	592x592x292	3300/50	15
NXDP V	Organics	287x592x292	1600/50	10
NXDP ABV	Bases, Acids, Organics	592x592x292	3300/140	20
NXDP ABV	Bases, Acids, Organics	287x592x292	1600/140	12

如有其他氣體, 也可諮詢當地的銷售團隊