



### ADVANTAGES

- Adjustable room side diffusion disc
- Gel seal between filter and housing
- Noise reducing rounded collar
- Welded housing
- Low Profile
- Room side replaceable HEPA filter module
- Housing can be installed from room and top side
- Gap free, architecturally pleasing room side surface

<b>Application</b>	Microelectronic, Hospitals, Life science
<b>Frame</b>	Anodized aluminium
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot-melt
<b>Sealant</b>	Polyurethane
<b>Max Temperature (°C)</b>	93° C
<b>Comment</b>	DOP efficiency: ≥ 99.99 Fire rating: UL 900 Housing Frame: Extruded aluminium Back plate: Hot dipped galvanized steel

Art. No.	Type	EN1822	Dimensions WxHxD (mm)	Filter size HxWxD (mm)	Con. Ø (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
15290001	Slimline RSR - 600*600	H13		600x600		4.5/121	4.7
15290002	Slimline RSR - 905*600	H13		600x905		680/120	6.6
15290003	Slimline RSR - 1210*600	H13		600x1210		947/119	7.9
4109001	SLM Housing 600*600* Ø250		600x600x133		250		9.72
4109002	SLM Housing 905*600* Ø305		905x600x133		305		9.8
4109003	SLM Housing 1210*600* Ø305		1210x600x133		305		9.91

\*Other dimensions, finishes and different options are available on request