



優勢

- 金屬框架、穩定牢固
- 大容塵量
- 可根據客戶需要定制非标尺寸
- 錐型袋口，優化氣流阻力

應用	空調通風系統, 初級過濾
外框	鍍鋅鋼
濾材	玻璃纖維
尺寸	過濾器截面尺寸(EN15805)
最大風量	1,25 x 額定風量
最高溫度(°C)	70°C
最大相對溼度	100%
安裝選項	可選擇正面緊壓或側面抽取式的安裝框架



料號	類型	EN779	ISO16890	尺寸W*H*D(mm)	風量/初阻力(m³/h/Pa)	袋數	重量(Kg)	能耗	能耗等級	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
3140085	A5	M5	ePM10 60%	592x592x600	3400/40	6	1,9	645	B	15	15	27	27	64
3140086	B5	M5	ePM10 60%	490x592x600	2800/40	5	1,6		B					
3140087	C5	M5	ePM10 60%	287x592x600	1700/40	3	1,1		B					
3140017	A6	M6	ePM2,5 50%	592x592x600	3400/70	6	1,9	1189	C	40	40	54	54	80
3140018	B6	M6	ePM2,5 50%	490x592x600	2800/70	5	1,6		C					
3140019	C6	M6	ePM2,5 50%	287x592x600	1700/70	3	1,1		C					
3100013	UF6	M6	ePM2,5 50%	592x592x600	3400/60	8	2,9	872	B	40	40	54	54	80
3100014	UG6	M6	ePM2,5 50%	490x592x600	2800/60	6	2,4		B					
3100015	UH6	M6	ePM2,5 50%	287x592x600	1700/60	4	1,5		B					
3140045	A7	F7	ePM1 60%	592x592x600	3400/85	6	1,9	1217	C	62	62	71	71	90
3140046	B7	F7	ePM1 60%	490x592x600	2800/85	5	1,6		C					
3140047	C7	F7	ePM1 60%	287x592x600	1700/85	3	1,1		C					
3100041	UF7	F7	ePM1 60%	592x592x600	3400/75	8	2,9	946	A	62	62	71	71	90
3100042	UG7	F7	ePM1 60%	490x592x600	2800/75	6	2,4		A					
3100043	UH7	F7	ePM1 60%	287x592x600	1700/75	4	1,5		A					
3105012	UF9	F9	ePM1 85%	592x592x600	3400/160	8	2,9	1956	D	87	87	91	91	98
3105013	UG9	F9	ePM1 85%	490x592x600	2800/160	6	2,4		D					
3105014	UH9	F9	ePM1 85%	287x592x600	1700/160	4	1,5		D					

能源消耗: 依據歐洲標準4/21-2018計算
 能源等級: 依據歐洲標準RS 4/C/001-2019