















ADVANTAGES

- Resistant to turbulence and extreme pressure drop
- Patented Aerodynamic support grid for lower pressure drop
- Optimized media area for the lowest pressure drop at EPA efficiency
- Hydrophobic filter construction and media
- Low operational pressure drop, even when wet, with patented built-in drainage
- Sealed on all sides and featuring our patented double sealing process

| Application | All installations where safety/reliability/long life is important, especially areas with high humidity/heavy rain Pre- or final filter for gas turbines, large industrial air compressors, diesel & gas engines, generators & enclosures, wind turbines | | | | | |
|--------------------------|---|--|--|--|--|--|
| Frame | Plastic moulded;ABS | | | | | |
| Gasket | Polyurethane, endless foamed | | | | | |
| Media | Glass fiber | | | | | |
| Separator | Hot-melt | | | | | |
| Sealant | Polyurethane | | | | | |
| Grille, Downstream | Support grid for filtermedia | | | | | |
| Rec. final pressure drop | 600 Pa | | | | | |
| Max airflow | 1,3 x nominal flow | | | | | |
| Max Temperature (°C) | 70°C | | | | | |
| Relative Humidity max | 100% | | | | | |
| Comment | Fire rating: Available according to DIN4102 class b2 rating on request Burst strength: > 6250 Pa continuous wet/soaked Reverse flow version: With support grid available on request Additional information: Also available in 1/2 and 3/4 size on request | | | | | |

CamGT 4V-300 is a high efficiency air inlet filter used for second and/or third stage filtration, depending on the gas turbine air inlet system. Typical range from M6 or MERV 11 up to E12 (EPA level), for the best gas turbine protection. Also available in versions with Fire rating DIN4102 class b2, Reverse flow, half-size and 3/4 size on request.

| Art. No. | Type | EN779 | EN1822 ASHRAE 52.2-2017 | ISO16890 | Dimensions WxHxD (mm) | Airflow/pressure drop (m³/h/Pa) | Weight (kg) | ePM1 | ePM1min | ePM2,5 | ePM2,5min | ePM10 |
|--------------|---------------|-------|-------------------------|------------|-----------------------|---------------------------------|-------------|------|---------|--------|-----------|-------|
| CGT1100111MY | CamGT 4V-300 | M6 | MERV 13 | Coarse 60% | 592x592x300 | 4250/105 | 8.0 | | | | | |
| CGT1101111MY | 4V-300-T7-Std | F7 | MERV 13 | ePM170% | 592x592x300 | 4250/130 | 8 | 72 | 72 | 80 | 80 | 93 |
| CGT1101211MY | 4V-300-T7-XL | F7 | MERV 13 | ePM170% | 592x592x300 | 4250/125 | 8.5 | 72 | 72 | 80 | 80 | 93 |
| CGT1102111MY | 4V-300-T8 | F8 | MERV 14 | ePM180% | 592x592x300 | 4250/140 | 8 | 80 | 80 | 87 | 87 | 96 |
| CGT1102211MY | 4V-300-T8-XL | F8 | MERV 14 | ePM180% | 592x592x300 | 4250/135 | 8.5 | 80 | 80 | 87 | 87 | 96 |
| CGT1103111MY | 4V-300-T9 | F9 | MERV 15 | ePM185% | 592x592x300 | 4250/165 | 8 | 85 | 84 | 89 | 89 | 96 |
| CGT1103211MY | 4V-300-T9-XL | F9 | MERV 15 | ePM185% | 592x592x300 | 4250/160 | 8.5 | 85 | 84 | 89 | 89 | 96 |
| CGT1104111MY | 4V-300-T10 | | E10 | | 592x592x300 | 4250/200 | 8.5 | 97 | 97 | 98 | 97 | 98 |
| CGT1105111MY | 4V-300-T11 | | E11 | | 592x592x300 | 4250/225 | 8.5 | | | | | |
| CGT1106111MY | 4V-300-T12 | | E12 | | 592x592x300 | 4250/260 | 9.0 | | | | | |

^{*}EPA Class in green frame and F class filter in black frame