



ADVANTAGES

- Strong and airtight frame
- Most convenient handling
- Optimized for Bag-in Bag-out safe change
- For very high velocity (up to 3,5 m/s)
- Lightest V-bank steel box filter in the industry

Application	Compact fine filter for air handling systems with high airflows
Frame	Galvanised steel
Gasket	Polyurethane
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Rec. final pressure drop	2x Initial pressure drop
Max airflow	1,1 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%



Art. No.	Type	EN779	ISO16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Area (m²)	Weight (kg)
OPR3621131000	OPR-E6-610x305x292-P	M6	ePM10 70%	610x305x292	2050/100	10.9	6
OPR6621121000	OPR-E6-610x610x292-P	M6	ePM10 70%	610x610x292	4500/100	22.0	9
OPR3721131000	OPR-E7-610x305x292-P	F7	ePM1 55%	610x305x292	2050/110	10.9	6
OPR6721121000	OPR-E7-610x610x292-P	F7	ePM1 55%	610x610x292	4500/110	22.0	9
OPR3821131000	OPR-E8-610x305x292-P	F8	ePM1 70%	610x305x292	2050/120	10.9	6
OPR6821121000	OPR-E8-610x610x292-P	F8	ePM1 70%	610x610x292	4500/120	22.0	9
OPR3921131000	OPR-E9-610x305x292-P	F9	ePM1 80%	610x305x292	2050/130	10.9	6
OPR6921121000	OPR-E9-610x610x292-P	F9	ePM1 80%	610x610x292	4500/130	22.0	9