

FILTER VALIDATION WITH CLEANSEAL

Challenge your Supply Air Terminal HEPA

A FULLY INTEGRATED SOLUTION

Cleanseal Integrity is an evolution of Camfil's Cleanseal platform to facilitate validation tests on high performance Terminal HEPA filters. This development supports:

- Centralized aerosol injection for groups of standard CleanSeal,
 Optionally additional local injection through the individual housing
- More efficient testing
- Versatility to adapt to any clean room design
- Risk mitigation compared to thermal aerosol generation

Cleanseal Integrity has been validated to comply with ISO14644-3 requirements

ADVANTAGES

- Prolonged HEPA filter lifetime by allowing low aerosol concentration
- Decreased fire risk by using cold aerosol generation, as well as avoiding upstream duct soiling
- Clean room Configuration adaptability by allowing for room side / technical side injection, in new built or retrofit projects
- Qualified aerosol injection with validated upstream concentration uniformity, allowing for testing by Discrete Particle Counter or Photometer, whether with DEHS or PAO
- Operator fail safe design by toolless operation.
 All connections deported in the control boxes, with space for connection identifiers
- Faster maintenance and operation by toolless design, quick & easy access, fast filter change
- Life Science grade quality with fully welded, pressure tested body and specific, H₂O₂ resistant coating

A FULLY INTEGRATED SOLUTION Only one operator required. Particle generator Particle generator Particle generator Particle generator Refect for retrofit or to reduce foreign equipment in the cleanroom. Two operators required.


AEROSOL INJECTION THROUGH THE HOUSING (for CleanSeal Integrity versions only)



Every standard CleanSeal includes a full suite of measurement ports for supply air filter validation. Integrity versions include additionally a dedicated self-sealing fitting for local aerosol injection and a qualified injection module (IntegriPod).

AEROSOL INJECTION THROUGH THE INTEGRIBOX

(for any standard CleanSeal)






FILTER VALIDATION WITH CLEANSEAL

Challenge your Supply Air Terminal HEPA

CLEANSEAL INTEGRITY IN DETAIL



All CleanSeal housings include a full suite of welded measurement ports for in-situ filter validation. They may be combined with the qualified IntegriPod aerosol injection device add-on, using the IntegriBox as injection port terminal.

CeanSeal Integrity are installation kits including the IntegriPod device, plus one additional local injection port (11) on the housing. IntegriBox terminals are optional.

- 1. IntegriPod injection add-on
- 2. Qualified stainless steel injection probe
- 3. EPDM double lip gasket for EUROVENT Class D connection
- 4. CleanSeal housing, fully welded body
- 5. Detachable mounting blocks for compression or suspension setup
- 6. Multi-position toolless filter clamping system (factory preset)
- 7. Multi-position filter retainer
- 8. Upstream pressure port P+ (room side access)
- 9. Secondary pressure ports P+/- for remote sensor hookup
- 10. Dedicated upstream Concentration port (room side access)
- 11. Self sealing fitting for local aerosol injection (Integrity version only)
- 12. Interchangeable front plate

INTEGRIPOD



The CleanSeal Integrity aerosol injection device is available for all standard housings types and for duct sizes:

D160 / D200 / D250 / D315 / D355

	Performance*	Requirements**
Aerosol concentration @0,45 m/s	15-25 μg/l	1-100 μg/l
Stability over time	<=8%	< <u>+</u> 10%
Relative STD deviation	<=8%	<20%
Relative MAX deviation	<=15%	<50%
Concentration ratio 100% sampling port vs. average	0,95 - 1,1	>0,75 < 1,25
Pressure drop	2 - 10 Pa	


^{*}depending on IntegriPod size

INTEGRIBOX



Service box with quick connect fittings for managing 1 to 5 CleanSeal housings. Versions for in or outside the clean room, wall or ceiling mounted. With flush door in CleanSeal design.

Particle injection loss for DEHS



^{**}acc. to IEST-RP-CC034-4 / ISO 14644-3