CLEANSEAL EXHAUST INTEGRITY





ADVANTAGES

- Toolless filter change for both HEPA and prefilter
- Built-in filter scaling option
- Robust fully welded construction for durable reliability and tightness
- High corrosion protection against decontamination agents
- Integrated scanning probe for qualified in-situ testing
- Toolless push-push door operation for immediate filter access
- Interchangeable exhaust door with or without prefilter

Application	Turbulent airflow in clean rooms and other controlled environments with qualified filter scanning requirements, for wall installation.
Installation Options	Universal mounting system for wall compression mounting, optional quick clamping kit and duct adapter rectangular-to-circular.
Comment	Construction: Steel, assembled from fully welded modules Finish: Decontamination resistant double-layer powder coat Standard color RAL 9010 (SW) or custom RAL Option: Stainless steel SS 304 (S4) or SS 316L (S6) Filters PU: MEGALAM MD(66mm)/(78mm)/MX(90mm)/MG(110mm) Control equipment: Room side accessible ports for downstream pressure, plus +/- secondary ports for remote pressure drop reading Integrated MIP manual filter scanning system Available in open plenum version For more information about compatible filters and air diffuser front plates, see the relevant product pages.

For the full standard product scope, see Customer Drawing downloads on the website.