
## **CLEANSEAL INTEGRITY**





## ADVANTAGES

- Complete interchangeable diffusion front plates range
- Robust fully welded construction for durable reliability and tightness
- High corrosion protection against decontamination agents
- Toolless filter clamping 100% secured and immediate
- Built-in filter scaling option
- Quick front plate locking for immediate access to the filter

Application	Turbulent airflow in clean rooms and other controlled environments with ISO 14644-3 filter testing requirements, for ceiling installation.
Installation Options	Universal mounting system for both suspended installation and compression mounting.
Comment	Construction: Steel, fully welded Finish: Decontamination resistant double-layer powder coat Standard color RAL 9010 (SW) or custom RAL Option: Stainless steel SS 304 (S4) or SS 316L (S6) Filter Gaskets: PU or GEL Filters PU: MEGALAM MD(66mm)/(78mm)/MX(90mm)/MG(110mm) Filters GEL: MEGALAM MD(71mm)/MX(105mm)/MG(115mm) Control equipment: Room side accessible upstream pressure port concentration port and aerosol injection, plus +/- secondary ports for remote dp reading. For more information about compatible filters and air diffuser front plates, see the relevant product pages Option: Damper, adjustable from the room

For the full standard product scope, see Customer Drawing downloads on the website.