₹camfil



- Come in a wide range of sizes.
- Can be pre-cut to size to suit particular applications and needs.
- High dust holding capacity.
- Strong, long-lasting, resilient coarse fibers.

Camfil CDM-600 media

Low resistance, economical synthetic media filter:

- Tackified synthetic, white
- 1" nominal thickness

Synthetic Media General Information

Camfil synthetic medias offer economical filtration for applications requiring thicknesses of 1 or 2 inches. Synthetic medias are available in various MERV ratings when evaluated per ASHRAE 52.2. Synthetic filters remove nuisance dust, lint, and airborne contaminants associated with straining and are primarily designed to protect equipment and act as prefilters. Synthetic medias utilize progressive density construction to increase the total dust holding capacity and are available in cut pads and bulk rolls. Synthetic media pads are available in dry (non-tackified), tackified, and dry-tack formats.

Shield HVAC systems and paint booths

Camfil synthetic medias are employed in commercial HVAC systems and can be used as prefilters in air handling units (AHUs) and in similar applications. They are also used as intake filters or prefilters for paint booths. Our media pads and rolls provide high dust arrestance and holding capacity, without shedding fibers into the airstream.

Prolong Final Filter Life

Synthetic medias reduce filter changeouts and operating costs by protecting high efficiency final filters. Camil medias trap larger particles upfront to bolster capturing capabilities of final filters, thus extending filter life. Complex Fibre Structure Expands Filter Surface Area Camfil medias are made into a pad or roll with a sizeable fiber surface area and a multitude of assorted fiber threads. The complex composition of the fibers catch more dirt and decreases resistance.



- For use as an intake filter in Downdraft booths, Semi-Downdraft
- booths and Prep Stations
- >96% initial efficiency for particles in the range of 7-10 microns on
- clean media
- CDM-600 supported in a wire frame
- Progressive Density Media enhances service life and dust holding
- capacity
- Temperature Rating: 212 degrees F (100 degrees C)

Performance & Dimensional Data





| Pads | | | Rolls | | | |
|---|--|---------------------------------------|--|--|----------|--|
| Part # | Standard Sizes | Case Qty | Part # | Standard Sizes | Case Qty | |
| Available upon request | | | Available upon request | | | |
| *Notes *Notes - Maximum width 85.5" (contact office for wider widths) -Maximum length 65.7' | | | | | | |
| Panel (CDMP-R1) | | | Cubes | | | |
| Part # | Standard Sizes | Case Qty | Part # | Standard Sizes | Case Qty | |
| 8201020 8202020 8202025 8201625 8202424 8202048 | 10 x 20 20 x 20 20 x 25 16 x 25 24 x 24 20 x 48 | 20 20 20 20 20 20 8 | Available upon request | | | |
| *Notes - Additional sizes available upon | request | | *Notes - Additional sizes and pocket co | otes dditional sizes and pocket configurations available upon request | | |

Pad Holding Frames

We also supply pad holding frames (PHF) to support our synthetic/fiberglass medias:

Long Service Life

- Rugged construction assures long service life with no maintenance
- No stress points to break or fracture
- U-channel design for perimeter frame

Built-in Safety

- No sharp edges to injure maintenance personnel
- Air entering grid is designed to guard against accidental puncturing

Easy Installation – No Bypass

- U-channel style frame holds the pad securely in place
- The easy open hourglass gate on the air entering side prevents sagging when fan is off

Camfil Canada Inc. | 2700 Steeles Ave. W Concord ON L4K 3C8 | 905.660.0688





ISO

www.camfil.com

Camfil has a policy of uninterrupted research, development and product improvement. We reserve the right to change designs and specifications without notice.

₹camfil