

## ₹camfil

## DURAFIL® ES<sup>3</sup> (ENERGY SAVER)

## **PRODUCT PERFORMANCE GUARANTEE**

The Camfil Durafil ES<sup>3</sup> (Energy Saver) comes fully guaranteed to outperform all competitive products of its kind and deliver the highest energy savings possible in the industry while maintaining rated efficiency. This guarantee eliminates associated risks with choosing or converting to the Durafil ES<sup>3</sup> and serves as proof that Camfil stands behind the product's design features and performance capabilities. The Durafil ES<sup>3</sup> is guaranteed to provide the following:

**HIGHEST ENERGY SAVINGS:** Due to the proprietary air filtration media of this product, it operates at a much lower pressure drop in an air handling system than any competitor's like product, resulting in energy savings that cannot be delivered by anyone else. Compared to other final filter configurations, the energy savings are even greater. Our Life Cycle Costing (LCC) modeling software can be used, in addition, to help optimize your energy reduction and filter life. This product is a 5-Star rated energy cost index filter.

**LIFETIME EFFICIENCY:** The Durafil ES<sup>3</sup> uses a special fine fiber media that guarantees the MERV rating will be maintained the entire time it is in a system, allowing consistent and sustainable clean, high-quality indoor air. Products made of highly charged coarse fiber media have been proven to have a rapid reduction in MERV rating once installed in an air handler.

**FILTER LIFE:** For the purpose of this document, based upon energy savings and filter dirt loading characteristics, the maximum life of the Durafil ES<sup>3</sup> shall be defined as two and a half times its initial resistance to airflow or three years – whichever comes first.

**CONDITIONS:** Guarantee is based upon not exceeding maximum rated airflow as prescribed by Camfil and not exceeding maximum operating temperature of 175° F (79° C). Filters are not to be used as moisture separators or exposed to heavy continuous loading of internally generated pollutants such as welding smoke, paint sprays, powders, or oil mist from manufacturing operations. Filters must be protected upstream with Camfil 30/30, or Dual 9 prefilters to qualify for the guarantee replacement.

The customer must contact Camfil to provide installation details. Requested information will include company name, shipping address, contact name, telephone number, the distributor that provided the filters, application information, previously used filter type/manufacturer, and a service life comparison description.

- Camfil will directly ship a complete set of replacement Durafil ES<sup>3</sup> filters to the customer up to a maximum quantity of 15 units.
- If the value of the replacement filters exceeds \$2000, a Camfil distributor or representative must visit the site to verify the information.
- Once the information has been verified in writing to Camfil, the replacement order will be shipped.
- A user may only qualify for one replacement set of filters.
- Disclaimers and exclusions that will apply include: Premature filter failure caused by mechanical damage or failure of the HVAC system; premature filter failure due to physical damage to the Durafil ES<sup>3</sup> caused by human intervention; premature filter failure due to application of the filter where differential pressure across the filter exceeds the published maximum recommended final pressure drop of 1.5" w.g.

## If the Durafil ES<sup>3</sup> does not perform to the above standards, Camfil promises to provide you with one free set of replacement filters.

Contact us at 1-866-4CAMFIL