## **EXTRACTION ARMS**





## **ADVANTAGES**

- Easy and stable positioning through grab handles and external swivels
- Integrated lighting in the capture hood (optional)
- Different length and diameters available
- Low static pressure and low noise level because of the smooth steel tubes
- Minimum internal dust deposits (no internal components)
- Low maintenance and easy cleaning

Camfil's extraction arms can be used to capture dust and fumes

Application	from various industrial applications like welding, grinding, cutting, polishing, painting or packaging (excluding chemically aggressive fumes and gases)
Installation Options	Workplace systems like Camfil's extraction arms easily can be connected to local exhaust ventilation systems or use a dedicated extraction an connection. From where, depending on the type of emissions, the process exhaust air is routed to a dust collector to get cleaned or ducted to the atmosphere where permitted.
Comment	Camfil 's workstations and extraction arms are built to last in industrial environments. Made of heavy duty, welded steel with powder coated surfaces, the systems are easy to install and require low maintenance over the lifetime. The arms are temperature resistance up to 80°C.  The CamArm extraction arms are available with 3 or 4 metre length in different diameters:  CamArm 160 Airflow range 900 – 1,400 m³/h (530 - 825 cfm)  160 mm dia (with 315 mm hood inlet)  CamArm 200  Airflow range 1,400 – 2,500 m³/h (825 - 1,470 cfm)  200 mm dia (with 350 mm hood inlet)