

















ADVANTAGES

- High availability and reliability
- Better fuel efficiency leads to lower CO2 emissions per MWh, when using EPA grades
- Hydrophobic EPA grades limit degradation such as fouling and corrosion
- Suitable for harsh environments
- Static air filter with long filter life and lower initial and stable pressure drop
- Lightweight construction for easy mounting
- Fully incinerable

| Application | All installations where safety/reliability/long life is important, especially areas with high humidity/heavy rain Pre- or final filter for gas turbines, large industrial air compressors, diesel & gas engines, generators & enclosures, wind turbines |
|--------------------------|--|
| Frame | Plastic moulded;ABS |
| Gasket | Polyurethane, endless foamed |
| Media | Glass fiber |
| Separator | Hot-melt |
| Sealant | Polyurethane |
| Grille, Downstream | Support grid for filtermedia |
| Rec. final pressure drop | 600 Pa |
| Max airflow | 1,3 x nominal flow |
| Max Temperature (°C) | 70°C |
| Relative Humidity max | 100% |
| Installation Options | In a separate bank, from the upstream or downstream sides. Can be close-coupled in a reverse-flow configuration |
| Comment | Additional product features: Hydrophobic filter construction and media High filtration efficiency (up to H13) Original vertical pleats with interrupted hot melt separator Sealed on all sides and featuring our patented double sealing process Resistant to turbulence and extreme pressure drop High burst strength >6250 Pa (>25") Solid HEPA frame eliminates air bypass Patented aerodynamic support grid for lower pressure drop Optimized media area for the low pressure drop at EPA efficiency Low operational pressure drop, even when wet, with patented built- in drainage Available in a reverse-flow configuration XL version is available on request. Fire rating: Available according to DIN4102 class b2 rating on request Reverse flow version: With support metal grid available on request Also available in 1/2 and 3/4 size on request. |

CamGT 4V-300 is a high efficiency air inlet filter used for second and/or third stage filtration, depending on the gas turbine air inlet system. Typical range from M6 or MERV 11 up to E12 (EPA level), for the best gas turbine protection. Also available in versions with Fire rating DIN4102 class b2, Reverse flow, half-size and 3/4 size on request.

| Туре | EN779 EN1822 | ISO 16890 | Dimensions WxHxD (mm) | Airflow/pressure drop (m³/h/Pa) | Media area (m² |) Weight (kg | ePM1 | ePM1mir | ePM2,5 | ePM2,5mii | n ePM10 | ASHRAE 52.2-2017 |
|---------------------|--------------|-----------|-----------------------|---------------------------------|----------------|--------------|------|---------|--------|-----------|---------|------------------|
| 4V-300-T7-Std | F7 | ePM170% | 592x592x300 | 4250/130 | 19 | 8 | 72 | 72 | 80 | 80 | 93 | MERV 13 |
| 4V-300-T7-XL | F7 | ePM170% | 592x592x300 | 4250/125 | 26 | 8.5 | 72 | 72 | 80 | 80 | 93 | MERV 13 |
| 4V-300-T8 | F8 | ePM180% | 592x592x300 | 4250/140 | 19 | 8 | 80 | 80 | 87 | 87 | 96 | MERV 14 |
| 4V-300-T8-XL | F8 | ePM180% | 592x592x300 | 4250/135 | 26 | 8.5 | 80 | 80 | 87 | 87 | 96 | MERV 14 |
| 4V-300-T9 | F9 | ePM1 85% | 592x592x300 | 4250/165 | 19 | 8 | 85 | 84 | 89 | 89 | 96 | MERV 15 |
| 4V-300-T9-XL | F9 | ePM1 85% | 592x592x300 | 4250/160 | 26 | 8.5 | 85 | 84 | 89 | 89 | 96 | MERV 15 |
| 4V-300-T10 | E10 | | 592x592x300 | 4250/200 | 29 | 8.5 | 97 | 97 | 98 | 97 | 98 | |
| 4V-300-T11 | E11 | | 592x592x300 | 4250/225 | 29 | 8.5 | | | | | | |
| 4V-300-T12 | E12 | | 592x592x300 | 3400/260 | 30 | 9.0 | | | | | | |
| 4V-300-T12-CamBrane | E12 | | 592x592x300 | | | | | | | | | |