



## Advantages

- Meets FDA requirements
- Ceramic frame
- Efficiency tested after precuring
- Efficiency tested after precuring
- Maximum continuous operating temperature 350°C, efficiency 99,99% at 0,3 #m
- Exclusive precuring process at 300°C carried out in the plant

**Application:** Protection of ultra-clean processes at high temperature, sterilisation tunnels in the pharmaceutical industry

**Type:** High temperature filter

**Frame:** Composite ceramic

**Gasket:** Glass Fiber

**Media:** Glass fiber

**Separator:** Glassfiber

**Sealant:** Ceramic

**Grille, Upstream:** Stainless steel

**Grille, Downstream:** Stainless steel

**Rec. final pressure drop:** 350 Pa

**Temperature max:** 350°C

**Mounting/Frames:** A stainless steel adaptor frame can be supplied to reach the thickness of 150mm or 292mm

Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /hr/Pa)	Media area (m <sup>2</sup> )	Weight (kg)	Initial eff. (%)
3P3	305x305x84	300/250	2,9	2	99.9
3P6	305x610x84	600/250	5,9	4	99.9
4P4	457x457x84	675/250	5	3	99.9
4P6	457x610x84	900/250	8,9	4	99.9
6P6	610x610x84	1200/250	12,1	5	99.9
7P6	762x610x84	1500/250	15,3	6	99.9
9P6	915x610x84	1800/250	18,5	8	99.9