



Advantages

- Fine fibre ensures that filter maintains its efficiency throughout its life in the system
- High dust holding capacity
- Suitable for variable airflow
- Robust design

Application: Built-up filter banks, rooftops, split systems, freestanding units, package systems and air handlers

Type: Compact Pleated Filter

Frame: Galvanised steel

Temperature max: 90

Media: Microfine glass media formed into full pack depth pleats separated by corrugated aluminum

Recommended final pressure drop: 450 Pa (suggested economical change point 250Pa)

Fire Rating: UL 900



Art. No.	Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Weight (kg)
2135001	3HCP8-65-242412 AEROPAC	592x592x292	3400/110	8.6
2135001	3HCP8-65-122412 AEROPAC	287x592x292	1700/110	6.4
2135001	3HCP8-85-242412 AEROPAC	592x592x292	3400/150	8.6
2135001	3HCP8-85-241212 AEROPAC	287x592x292	1700/150	6.4
2135001	3HCP8-95-242412 AEROPAC	592x592x292	3400/160	8.6
2135001	3HCP8-95-241212 AEROPAC	287x592x292	1700/160	6.4
2135001	3CPMHF-122412-60	287x592x292	1700/95	6.4
2135001	3CPMHF-242412-60	592x592x292	3400/95	8.6
2135001	3CPMHF-242412-90	592x592x292	3400/130	8.6
2135001	3CPMHF-122412-90	287x592x292	1700/130	6.4
2135001	3CPMHF-242412-95	592x592x292	3400/155	8.6
2135001	3CPMHF-122412-95	287x592x292	1700/155	6.4