

Advantages

- Multi-pocket bag filter
- Robust metal header frame
- Available in a range of efficiencies
- Comprehensive range of standard sizes
- Unique pocket design

Application: Air conditioning applications

Type: Bag Filter

Frame: Galvanised steel

Media: Synthetic

Rec. final pressure drop: 450

Temperature max: 70

Mounting frames: Holding frames: Front and side access housings and frames are available, Type 8 and FC Housings

Recommended final pressure drop: 450 Pa (suggested economical change point 250 Pa)

Fire rating: UL 900



Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Bags	Weight (kg)
A5	600x592x592	3400/75	6	2.4
B5	600x490x592	2700/75	5	2
C5	600x287x592	1700/75	3	1.5
A6	600x592x592	3400/100	6	2.4
B6	600x490x592	2800/100	5	2
C6	600x287x592	1700/100	3	1.5
A7	600x592x592	3400/110	6	2.4
B7	600x490x592	2800/110	5	2
C7	600x287x592	1700/110	3	1.5
AB	600x592x592	3400/145	6	2.4
B8	600x490x592	2800/145	5	2
CB	600x287x592	1700/145	3	1.5