Cleanseal Extract Exhaust/Return Air Housing

Advantages

- Tool-less filter clamping 100% secured and immediate
- Long lasting reliability and tightness: robust fully welded construction
- Ensure localized control of potent compounds, eliminating the contamination of downstream ductworks
- Quick grid locking for immediate access to filter
- High corrosion protection againts decontamination agents
- Easily operation with scanning system for filter integrity test

Application:CleanSeal Extract is wall mount equipment used for exhaust/return air system: Pharmaceutical, Biotechnology, Chemistry, Hospitals, and animal facilities.

Type: Housing

Type: Fully welded Wall mount housing.

Construction: Carbon steel, fully welded seams, accessories in

Stainless Steel

Finish: 3 Steps · white epoxy coated RAL 9010, qualified for high

corrosion protection against decontamination agents

Filter Seal: Endless PU gasket on filter.

Connection: Rectangular pre-drilled flanges.

Pressure Gauge: Pressure gauge is pre-installed on the equipment. **Performance:** The whole equipment could bear ±1000Pa. The overall leakage rate should no more than 0.25% per hour under

1000Pa pressure.

Scanning system: Accourding to standard IS014644-3.

Model Name	Dimensions WxHxD (mm)	Filter size HxWxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Weight (kg)
CLE-SW-6P6-P-MD- SR6008-N-LS-A000	800x998x526	610x610x66		55
CLE-SW-6P6-P-MX- SR6008-N-LS-A000	800x998x526	610x610x90		55
CLE-SW-6P6-P-MG- SR6008-N-LS-A000	800x998x526	610x610x110		55
CLE-SW-6P6-P-48MD- SR6008-N-LS-A000	800x998x526	610x610x66		55
CLE-SW-6P6-P-NF- SR6008-N-LS-A000	800x998x526	0x0x0		55
Megalam MDA-610x610-01/22	610x610x66	610x610x66	100/250	4
Megalam MXA-610x610-01/22	610x610x90	610x610x90	1500/250	5.6
Megalam MGA-610x610-01/22	610x610x110	610x610x110	1800/250	5.3
*Other model please contact Camfil Kunshan factory.				