



Advantages

- Patented HemiPleat™ technology- proven open
- Each filter set is shipped together in one carton
- Self-cleaning air filter cartridges
- Suitable also in high humidity conditions
- Increased air to cloth ratio thanks to Hemi-Pleat™ technology.
- Water repellent media protected by metal liners
- Galvanized metal finish
- Improved air distribution
- Suitable as prefilter for filter class E10, E12

Application:For desert/dry/ heavy dust load areas

Type:Pleated Cylinder

Media:Polytech HE

Temperature max:70° C

Pleat:HemiPleat

Additional information: Available as dimple pleated and in fire retardant version on request.



Camfil CamPulse with proven HemiPleat™ technology, combined with a synthetic media, delivers valuable benefits to gas turbine operation and maintenance.

| Type | EN779 | Length (mm) | Diameter (mm) | Length 2 (mm) | Diameter 2 (mm) | Air Flow/ pressure drop (m³/h/Pa) | Area (m²) | Weight (kg) | Initial efficiency |
|------|-------|-------------|---------------|---------------|-----------------|-----------------------------------|-----------|-------------|--------------------|
| CoCy | F7 | 660 | 324 | 660 | 445 | 2500/165 | 34,7 | 12,8 | 94 |

CyCy = Large Cylindrical, Small cylindrical
CoCy= Large Conical, Small Cylindrical