

ECO Moisture Separator

Advantages

- Pre-drilled weeping holes for drainage or reclaim of valuable process oils
- Optional coalescer pad available for increased efficiency

Application: High moisture situations in commercial or industrial processes, or oil-laden industrial applications. Includes weeping holes for drainage or reclaim of airborne oil or mists.

Type: Metal Panel

Rec. final pressure drop: 250

Efficiency: 98%+ on droplets 20 microns and larger

Airflow operating range: Velocity of 2.25 m/s to 2.75 m/s, consult factory outside of this range.

Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
EcoMoister-For built-up banks	289x594x95	1700/	4,5
EcoMoister-For built-up banks	594x289x95	1700/	4,5
EcoMoister-For side access housings(includes sealing gasket on vertical side)	594x594x95	3400/	8,6
EcoMoister-For side access housings(includes sealing gasket on vertical side)	289x594x95	1700/	4,5
EcoMoister-For side access housings(includes sealing gasket on vertical side)	594x289x95	1700/	4,5
EcoMoister-For built-up banks	594x594x95	3400/	8,6
EcoMoister-For built-up banks	594x289x95	1700/	4,5
EcoMoister-For built-up banks	289x594x95	1700/	4,5
EcoMoister-For side access housings(includes sealing gasket on vertical side)	594x594x95	3400/	8,6
EcoMoister-For side access housings(includes sealing gasket on vertical side)	594x289x95	1700/	4,5
EcoMoister-For side access housings(includes sealing gasket on vertical side)	289x594x95	1700/	4,5
EcoMoister-For built-up banks	594x594x95	3400/	8,6