

# CamGT Box Type Green II



## Advantages

- Ensures water drainage
- Low pressure drop also in wet conditions
- Easy mounting
- High filtration efficiency
- Resistant to turbulence and high pressure drop
- Water resistant media

**Application:** All installations where safety/reliability is important

**Type:** Compact Pleated Filter

**Frame:** Plastic moulded

**Gasket:** Polyurethane, endless foamed

**Media:** Glass fiber

**Separator:** Hot Melt Separator Technology

**Rec. final pressure drop:** 600 Pa

**Temperature max:** 70°C

**Additional information:** XL version available on request. Profile placed at 292 mm depth for clamping, i.e for fastener spring type C-80.



CamGT Box Type Green is a high-capacity filter for turbomachinery. Thanks to the unique design, its performance is maintained in humid or wet conditions, guaranteeing a long lifetime and a good filter economy.

| Type | EN779 | EN1822 | Dimensions WxHxD (mm) | Air Flow/pressure drop (m³/h/Pa) | Media area (m²) | Weight (kg) | Initial eff. (%) | ME (%)* |
|------|-------|--------|-----------------------|----------------------------------|-----------------|-------------|------------------|---------|
| Std  | F7    |        | 592x592x315           | 4250/115                         | 19              | 7,6         | 60               | 60      |
| Std  | F8    |        | 592x592x315           | 4250/140                         | 19              | 7,6         | 72               | 72      |
| Std  | F9    |        | 592x592x315           | 4250/145                         | 19              | 7,6         | 81               | 81      |
| Std  |       | E10    | 592x592x315           | 4250/215                         | 19              | 7,6         | 88               | 87,5    |

ME%: Minimum efficiency ref. to EN779:2012