

## Advantages

- High air flow rates
- High filter surface area offers low pressure drop for energy savings and longer life
- With stand high temperature up to 120°C
- Large media area

**Application:** Industry and hospitals

**Type:** V-Bank Box Filter

**Frame:** Galvanised steel

**Gasket:** Neoprene

**Media:** Glass fiber

**Separator:** Glassfiber

**Sealant:** Polyurethane

**Temperature max:** 120°C

**Mounting/Frames:** Mounting systems: FCBL-A housing

**Gasket:** Half-round neoprene Ø 15 mm moulded in one piece, 99.995% MPPS (H13 according to EN 1822), 99.99 % 0.3#

**Temperature:** 120°C maximum continuous



Art. No.	Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Weight (kg)
1561.02.00	SFR120-E-4000-H13	610x610x292	4000/250	23
1561.01.00	SFR120-E-3400-H13	610x610x292	3400/250	20
1564.01.00	SFR120-E-2500-H13	610x610x292	2500/250	19
1566.01.00	SFR120-E-1500-H13	305x610x292	1500/250	13
1567.01.50	SFR120-E-3200-H13	595x595x292	3200/250	22
1568.01.50	SFR120-E-1300-H13	289x595x292	1300/250	12