



## Advantages

- Optimized media surface by conical pocket shape
- Robust construction
- High dust holding capacity
- Easy installation
- Robust metal header frame

**Application:** Prevention of dust and dirt build up on heating/cooling coils within ventilation systems

**Type:** Bag Filter

**Frame:** Galvanised steel

**Media:** Synthetic

**Dimensions:** Filter front dimensions according EN 15805

**Rec. final pressure drop acc. EN 13053:** 150 Pa

**Maximum airflow:** 1,25 x nominal flow

**Temperature max:** 70°C

**RH. max:** 100%

**Mounting frames:** Front and side access housings and frames are available, Type 8 and FC Housings

**Fire rating:** DIN 53438 class F1

EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Bags	Area (m <sup>2</sup> )	Weight (kg)
G4	Coarse 60%	592x592x360	3400/40	6	2,6	2,2
G4	Coarse 60%	490x592x360	2800/40	5	2,2	1,9
G4	Coarse 60%	287x592x360	1700/40	3	1,3	1,3
G4	Coarse 60%	592x592x580	3400/30	6	4,2	2,6
G4	Coarse 60%	490x592x580	2800/30	5	3,5	2,2
G4	Coarse 60%	287x592x580	1700/30	3	2,0	1,5

*Other dimensions are available on request - All dimensions are nominal*