



Advantages

- Optimized media surface by conical pocket shape
- Robust construction
- High dust holding capacity
- Easy installation
- Robust metal header frame

Application: Prefilter for air conditioning and ventilation systems

Type: Bag Filter

Frame: Galvanised steel

Media: Synthetic

Dimensions: Filter front dimensions according EN 15805

Rec. final pressure drop acc. EN 13053: 150 Pa

Maximum airflow: 1,25 x nominal flow

Temperature max: 70°C

RH. max: 100%

Mounting/Frames: Front and side access housings and frames are available



Art. No.	Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Bags	Area (m²)	Weight (kg)
3200005	HC66/360	G4	Coarse 60%	592x592x360	3400/40	6	2,6	2,2
3200006	HC56/360	G4	Coarse 60%	490x592x360	2800/40	5	2,2	1,9
3200007	HC36/360	G4	Coarse 60%	287x592x360	1700/40	3	1,3	1,3
3202009	HC66/580	G4	Coarse 60%	592x592x580	3400/30	6	4,2	2,6
3202033	HC56/580	G4	Coarse 60%	490x592x580	2800/30	5	3,5	2,2
3202016	HC36/580	G4	Coarse 60%	287x592x580	1700/30	3	2,0	1,5

Other dimensions are available on request - All dimensions are nominal

