



## Advantages

- High dust holding capacity
- Tapered pockets
- Incinerable bags
- Resistant media
- Low pressure drop

**Application:** Installations exposed to turbulence and/or recurrent high humidity

**Type:** Bag Filter

**Gasket:** Polyurethane

**Media:** Synthetic

**Rec. final pressure drop:** 250 Pa

**Temperature max:** 70°C



Hi-Cap GT is a high quality filter, available for the removal of coarse particles. It allows for a secure and efficient filtration in industrial environments where large amounts of dust are present. Long experience and continuous R&D has optimised the product for impressive filtration at a low cost.

| Type   | Material         | EN779 | Dimensions WxHxD (mm) | Air Flow/pressure drop (m³/h/Pa) | Bags | Media area (m²) | Weight (kg) |
|--------|------------------|-------|-----------------------|----------------------------------|------|-----------------|-------------|
| HC66   | Galvanised steel | G4    | 592x592x360           | 3400/40                          | 6    | 2,7             | 1,7         |
| XLS4   | Plastic          | G4    | 592x592x370           | 3400/40                          | 6    | 2,7             | 1,0         |
| XLT    | Plastic          | G4    | 490x490x370           | 3400/35                          | 8    | 2,9             | 1,2         |
| Hi-Cap | Galvanised steel | G4    | 592x592x195           | 3400/45                          | 8    | 1,8             | 1,6         |
| XLS4   | Plastic          | G4    | 592x592x520           | 3400/35                          | 6    | 3,7             | 1,2         |
| Hi-Cap | Galvanised steel | G4    | 592x592x580           | 3400/35                          | 6    | 4,1             | 2           |

*Hi-Cap other dimensions available on request*