



Advantages

- Rigid self supporting pockets
- High mechanical strength
- High dust holding capacity
- Robust plastic header frame
- Welded pocket construction
- No metal parts

Application: Comfort air conditioning applications, gas turbines.

Type: Bag Filter

Gasket: Polyurethane

Media: Synthetic

Rec. final pressure drop: 250 Pa

Temperature max: 70°C

Mounting frames: Front and side access housings and frames are available, Type 8 and FC Housings



Hi-Cap GT is a high quality filter, available for the removal of coarse particles. It allows for a secure and efficient filtration in industrial environments where large amounts of dust are present. Long experience and continuous R&D has optimised the product for impressive filtration at a low cost.

Material	EN779	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Bags	Area (m ²)	Weight (kg)
Galvanised steel	G4	592x592x360	3400/40	6	2,7	1,7
Plastic	G4	592x592x370	3400/40	6	2,7	1,0
Plastic	G4	490x490x370	3400/35	8	2,9	1,2
Galvanised steel	G4	592x592x195	3400/45	8	1,8	1,6
Plastic	G4	592x592x520	3400/35	6	3,7	1,2
Galvanised steel	G4	592x592x580	3400/35	6	4,1	2

Hi-Cap other dimensions available on request