



Advantages

- Low pressure drop
- Light weight construction
- Fully incinerable
- Easy mounting
- Improves overall filter economy

Application: Suitable for demanding operating conditions like heavy polluted rural or industrial areas

Type: Compact Pleated Filter

Frame: Plastic moulded

Gasket: Polyurethane, endless foamed

Media: Glass fiber

Separator: Hot Melt Separator Technology

Rec. final pressure drop: 450 Pa

Temperature max: 70°C



The CamPGT is an energy efficient solution functioning as a high efficiency filter in Camfil medium velocity multistage inlet houses. It is intended for inland industrial and rural areas. Its unique geometry provides a large inlet area and optimized air flow, thus offering a lower pressure drop than industry standard for V-shaped barrier filters.

Model Name	EN779	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
CamPGT 4H-300 Std	F7		592x592x292	4250/95	17	4,3
CamPGT 4H-300 Std	F8		592x592x292	4250/110	18	4,3
CamPGT 4H-300 Std	F9		592x592x292	4250/125	19	4,3
CamPGT 4H-300 Std		E10	592x592x292	4250/200	24	4,3

XL versions available on demand