

## Fordeler

**Rec. final pressure drop:**250 Pa

**Temperatur maks.:**70°C maximum in continuous service



Modellnavn	EN779	ISO16890	Dimensjoner BxHxD (mm)	Air Flow/trykkfall (m <sup>3</sup> /t/Pa)	Antall sylindere	område (m <sup>2</sup> )	Vekt (kg)
Aeropleat III 20x16x2	G4	ePM10 65%	394x495x44	1887/70	1887	0.6	0.4
Aeropleat III 20x20x2	G4	ePM10 65%	495x495x44	2363/70	2363	0.8	0.4
Aeropleat III 25x20x2	G4	ePM10 65%	495x622x44	2950/70	2950	1.0	0.6
Aeropleat III 25x16x2	G4	ePM10 65%	394x622x44	2363/70	2363	0.73	0.5
Aeropleat III 24x24x2	G4	ePM10 65%	594x594x44	3400/70	3400	1.13	0.65
Aeropleat III 24x12x2	G4	ePM10 65%	289x594x44	1656/70	1656	0.57	0.35
Aeropleat III 24x20x2	G4	ePM10 65%	495x597x44	2839/70	2839	0.96	0.55
Aeropleat III 24x18x2	G4	ePM10 65%	444x597x44	2550/70	2550	0.85	0.5
Aeropleat III 24x24x4	G4	ePM10 65%	594x594x95	3400/50	3400	2.11	1.2
Aeropleat III 24x12x4	G4	ePM10 65%	289x594x95	1700/50	1700	1.05	0.65
Aeropleat III 20x20x4	G4	ePM10 65%	492x492x95	2336/50	2336	1.46	0.9
Aeropleat III 20x16x4	G4	ePM10 65%	390x492x95	1853/50	1853	1.17	0.75
Aeropleat III 25x16x4	G4	ePM10 65%	390x619x95	2332/50	2332	1.46	0.9
Aeropleat III 24x20x4	G4	ePM10 65%	492x594x95	2768/50	2768	1.76	1.05