



## Advantages

- Available for all kind of applications

**Application:** For use as a pre filter in air conditioning, and spraybooth ventilation

**Type:** Media Roll

**Rec. final pressure drop:** 150 Pa

**RH. max:** 100%

Art. No.	Model Name	Type	Media	EN779	ISO16890	Dimensions WxHxD (mm)	Dimensions WxL (m)	Media Thickness (mm)	Weight (g/m <sup>2</sup> )	Air Flow/ pressure drop (m <sup>3</sup> /h/Pa)	Pressure drop (Pa)	Area (m <sup>2</sup> )	Weight (kg)	Velocity (m/s)
5200003		CM-355	Synthetic	G3	Coarse 50%	xx	2,0x20	10-12	150	/30	30		6,5	1.0
5200006		CM-360	Synthetic	G3	Coarse 50%	xx	2,0x20	8-10	190	/45	30		8,0	1.0
5200013		CDM-600	Synthetic	M5	Coarse 85%	xx	2,0x20	23-25	600	/85	85		24,5	1.0
5404511	FCF 24x12x1-G3		Synthetic	G3	Coarse 50%	597x292x22	1x20	10		1700/144		0,174	1,57	
5404002	FCF 24x12x1-G4			G4	Coarse 60%	597x292x22	x			1700/190		0,174	1,29	
5404501	FCF 24x24x1-G3			G3	Coarse 50%	597x597x22	x			3400/115		0,356	1,35	
5404001	FCF 24x24x1-G4			G4	Coarse 60%	597x597x22	x			3400/140		0,356	1,39	
5200015		CDM-600		M5	Coarse 85%	xx	1.7x20			/85			24,5	1.0

*Other sizes and cut pads available on request.*

*Depth: Deviation possible.*

*Efficiency @ 5µm = 98%*