



Advantages

- Filter cells are made from aluminium, galvanised or stainless steelwire woven into a special pattern
- Grease and oil filter with very high separation efficiency.
- Can be cleaned in dishwasher or pressure washer.
- Prefilter suitable for cleanable dust, sand, flour, paint, oil
- Can be made in all customised sizes
- Very large cooling surface without excessive air resistance

Application: Metal filter for grease or oil mist separation. Prefilter for thick particles

Type: Metal Panel

Frame: Stainless steel AISI 304L, 316L

Type: G2 Metal filter and high oil separation efficiency.

Frame: Aluminium EN-AW-6060, ALMG3, stainless steel AISI 304L, acid stainless steel AISI 316L, galvanized.

Media: Woven metal wire mesh. Can be made in aluminium, galvanized, stainless steel or acid stainless steel material.

Grating: Aluminium, Hot-dip galvanized expanded metal net or stainless steel grid.

Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
camMet 25 mm	G2	Coarse 30%	592x592x25	3000/30	0,35	3,3
camMet Alu 25 mm	G2	Coarse 30%	592x592x25	3000/35	0,35	2,5
camMet 50 mm	G3	Coarse 40%	592x592x50	3000/35	0,35	5,5
camMet Alu 50 mm	G3	Coarse 40%	592x592x50	3000/45	0,35	4
camMet 100 mm	G4	Coarse 60%	592x592x100	3000/60	0,35	9,1
camMet Alu 100 mm	G4	Coarse 60%	592x592x100	3000/60	0,35	6,6

Other dimensions on demand

Height = 100->750

Width = 100->1500

Depth 8,5->150 (galvanised 10->150)

