



Advantages

- High air flow
- Low pressure drop
- Optimize the air filtration in clean rooms
- Applicable up to 5000 m³/h air flow
- Ergonomic handle

Application: Efficiency final filtration in air conditioning systems, housings and diffusers

Type: V-Bank Box Filter

Frame: Galvanised steel

Gasket: EPDM

Media: Glass fiber

Separator: Hot Melt

Sealant: Polyurethane

EN 1822 (Efficiency @ MPPS): E10(≥85%), E11(≥95%),

E12(≥99,5%)

Rec. final pressure drop: 2x Initial pressure drop

Max. final pressure drop: 600 Pa

Temperature max: 70°C

RH. max: 100%

Mounting/Frames: FKB, FKB/D, CamBox

Remarks: Special versions on request (e.g. stainless steel frame or high temperature version 120°C)

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
VEXL10-289x595x292-M	E10	289x595x292	1700/250	16	8,5
VEXL10-305x610x292-M	E10	305x610x292	2000/250	14	8,5
VEXL10-595x595x292-M	E10	595x595x292	4200/250	38	13
VEXL10-610x610x292-M	E10	610x610x292	4000/250	21	13
VEXXL11-305x610x292-M	E11	305x610x292	2000/250	14	14
VEXXL11-610x610x292-M	E11	610x610x292	5000/250	35,5	23
VEXL12-289x595x292-M	E12	289x595x292	1300/250	16	12
VEXL12-305x610x292-M	E12	305x610x292	1500/250	16	8,5
VEXL12-595x595x292-M	E12	595x595x292	3200/250	38	22
VEXL12-610x610x292-M	E12	610x610x292	4000/250	40	16,5