



Advantages

- Leak-free installation ensures maximum possible efficiency
- Lowest possible Life Cycle Cost (LCC)
- Rapid bayonet fitting system and integral dual TPE gaskets
- Reduced weight compared to Metal version
- 360 degree geometry and even air distribution ensures maximum possible lifetime
- May be filled with a wide range of molecular filtration medias
- Totally corrosion resistant
- Modular and flexible assembly

Application: The most reliable molecular filter for high efficiency and long-term control of molecular contaminants in sensitive buildings and process industries

Type: Loose Fill Cylinder

Frame: Plastic moulded

Gasket: Double seal, molded TPE

Temperature max: 40°C

RH. max: 70%

Mounting/Frames: Dedicated base plate in 3 standard sizes (see separate page)

Type	Adsorbent type	Length (mm)	Diameter (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
CG 1300	CEX003	240	147	1250/80	1,55
CG 2600	CEX003	450	147	2500/135	2,85
CG 3500	CEX003	600	147	3400/175	3,75
CG 1300	LGS048	240	147	1250/60	1,55
CG 2600		450	147	2500/100	2,85
CG 3500		600	147	3400/165	3,75
CG 1300	CamPure 8	240	147	1250/80	2,4
	CamPure 8	450	147	2500/135	4,4
CG 3500	CamPure 8	600	147	3400/175	5,7

Other adsorbents available on request

Airflow and dp values stands for 16 cylinders on a 610x610 base plate