



Advantages

- May be filled with any molecular filtration media
- Vibrated fill technique to prevent media settlement
- Galvanised steel frame, option for stainless steel
- May be lined with a fine scrim to minimise shedding
- Standard and non-standard sizes available
- Plastic frame for certain standard sizes

Application: Adsorption of odours and gases in air conditioning applications

Type: Loose fill Panel

Media: Activated Carbon

Temperature max: 40°C

RH. max: 30% - 70%

Mounting/Frames: Front and side access housings and frames are available

Available in standard and custom sizes, CamCarb PM panels are high-quality molecular filtration panels for use in a variety of housings.

CamCarb PM panels may be filled with many different molecular filtration media to protect people, processes, the environment and cultural artefacts.

CamCarb PM panels are a cost-effective method to deploy moderate amounts of carbon media.

The standard construction is galvanized steel with stainless steel as an option. Both face meshes are fitted with internal scrims to eliminate shedding of fine particles and minimize dusting.

Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Carbon Volume (L)	Weight (kg)
600x600x25	350/30	9	5,5
300x600x25	175/30		
500x600x25	300/30		
600x600x50	350/60	18	11
300x600x50	175/60		
500x600x50	300/60		

Filters are available in a comprehensive range of sizes and depths. Please contact Camfil for more information.