



## Advantages

- Low pressure drop
- High media cleanliness
- Wide range of dimensions

**Application:** Clean room recirculation air, clean room make up air

**Type:** Box Filter

**Sealant:** Polyurethane

**Temperature max:** 40°C

**RH. max:** 70%

**Particle cleanliness:** ISO Class 6

**Gasket:** 01 = downstream, 10 = upstream

**Outgassing:** Individually outgassing tested for VOC emissions on request

Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Weight (kg)
610x610x292	2600/60	15
305x610x292	1100/60	8
595x595x292	2600/60	15
289x595x292	1100/60	8
592x592x292	2600/60	15
287x592x292	1100/60	8
610x610x292	2600/60	15
305x610x292	1100/60	8
595x595x292	2600/60	15
289x595x292	1100/60	8
592x592x292	2600/60	15
287x592x292	1100/60	8
610x610x292	2600/60	15
305x610x292	1100/60	8
595x595x292	2600/60	15
289x595x292	1100/60	8
592x592x292	2600/60	15
287x592x292	1100/60	8
610x610x292	2600/60	15
305x610x292	1100/60	8
595x595x292	2600/60	15
289x595x292	1100/60	8
592x592x292	2600/60	15
287x592x292	1100/60	8

*For media choice, please refer to GigaPleat NXPH*