



Advantages

- Clip-on design
- High strength plastic frame
- Can be fitted directly to a final filter
- Optimal coalescing performance
- Downstream pleat separators

Application: Suitable for most areas including wet and coastal

Type: Pleated Panel

Frame: Plastic moulded

Gasket: Polyurethane, endless foamed

Rec. final pressure drop: 400 Pa

Temperature max: 70°C

Mounting/Frames: Integrated clip on / optional without clip.

Separate metal clips available

Additional information: External dimensions Std. 598x604x129.



The Camfil CamClose is primarily used as a pre-filter to extend the service life of final filters by offering low initial pressure drop and high dust capacity. The filter is specially suitable for applications in humid conditions, like tropical and coastal installations, thanks to its downstream pleat separators and built-in drainage.

CamClose clips on CamGT and Opakfil.

Type	Media	EN779	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
Compact	Synthetic	G4	592x592x96	3400/50	2,6	2,5
Standard	Synthetic	G4	592x592x129	3400/50	2,6	2,5
Compact	Glass fiber	M6	592x592x96	3400/75	13	4,3
Standard	Glass fiber	M6	592x592x129	3400/75	13	4,3