



Advantages

- Lowest cost of ownership for a MERV 13 filter in a pleated panel design
- Pleated panel filter for meeting LEED requirements
- High wet-strength beverage board frame
- Available in 2" and 4" depths

Application: Prefilters to higher efficiency filters, stand-alone filters for rooftops, split systems, free-standing units and package systems and air handlers

Type: Pleated Panel

Frame: Rigid water resistant cardboard

Media: Synthetic

Dimensions: Filter front dimensions according EN 15805

Rec. final pressure drop acc. EN 13053: 250 Pa

Temperature max: 70°C

Fire rating: UL 900

Art. No.	Model Name	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Area (m ²)	Weight (kg)
540F-FG405413005	AP-THIRTEEN 24x24x2	F7	ePM2,5 80%	594x594x44	3400/100	1.6	0.68
540F-FG405413006	AP-THIRTEEN 24x12x2	F7	ePM2,5 80%	289x594x44	1700/100	0.8	0.4
540F-FG405413007	AP-THIRTEEN 24x20x2	F7	ePM2,5 80%	495x594x44	2839/100	1.3	0.58
540F-FG405414001	AP-THIRTEEN 24x24x4	F7	ePM2,5 80%	594x594x95	3400/85	2.6	1.25
540F-FG405414002	AP-THIRTEEN 24x12x4	F7	ePM2,5 80%	289x594x95	1700/85	1.3	0.67
540F-FG405414007	AP-THIRTEEN 24x20x4	F7	ePM2,5 80%	492x594x95	2839/85	2.1	1.04