



Advantages

- Ensures water drainage
- Low pressure drop also in wet conditions
- Easy mounting
- Water resistant media
- High filtration efficiency
- Resistant to turbulence and extreme pressure drop
- Meets the industry's latest and most stringent requirements

Application: All installations where safety/reliability is important

Type: Compact Pleated Filter

Frame: Plastic moulded

Gasket: Polyurethane, endless foamed

Media: Glass fiber

Separator: Hot Melt

Sealant: Polyurethane

Grille, Downstream: Support grid for filtermedia

Rec. final pressure drop: 600 Pa

Temperature max: 70°C

Fire rating: Available according to DIN4102 class b2 rating on request

Burst strength: > 6250 Pa continuous wet/soaked

Reverse flow version: With support grid available on request

Additional information: Also available in 1/2 and 3/4 size on request.



CamGT 4V-300 is a high efficiency air inlet filter used for second and/or third stage filtration, depending on the gas turbine air inlet system. Typical range from M6 or MERV 11 up to E12 (EPA level), for the best gas turbine protection. Also available in versions with Fire rating DIN4102 class b2, Reverse flow, half-size and 3/4 size on request.

Art. No.	Type	EN779	EN1822	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Area (m²)	Weight (kg)	Initial efficiency	Minimum efficiency
CGT0101111MY	Std	F7		ePM1 75%	592x592x292	4250/135	19	8	58	57
CGT0101211MY	XL	F7		ePM1 75%	592x592x292	4250/125	26	8,5	55	55
CGT0102111MY	Std	F8		ePM1 80%	592x592x292	4250/145	19	8	70	70
CGT0102211MY	XL	F8		ePM1 80%	592x592x292	4250/135	19	7	71	71
CGT0103111MY	Std	F9		ePM1 85%	592x592x292	4250/170	19	8	81	80
CGT0103211MY	XL	F9		ePM1 85%	592x592x292	4250/160	26	8,5	81	81
CGT0106111MY	Std		E12		592x592x292	4250/310	29	9		
	Std		H13		592x592x292	3400/330	30	9		

ME%: Minimum efficiency ref. to EN779:2012