



Advantages

- Moisture resistant frame board
- Radial Pleats
- Welded Steel Grid with Corrosion Inhibitor
- Diagonal Support
- Proprietary Dual High Lofted Fibers
- Built Strong

Application: Prevention of dust and dirt build up on heating/cooling coils within ventilation systems

Type: Pleated Panel

Frame: Rigid water resistant cardboard

Media: Dual layered, blended polyester

Rec. final pressure drop acc. EN 13053: 200 Pa

Temperature max: 70°C

Mounting frames: Front and side access housings and frames are available.

Fire rating: UL 900



Model Name	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Area (m ²)	Weight (kg)
24x24x2	ePM10 50%	594x594x44	3400/75	1.56	0,8
24x20x2	ePM10 50%	495x597x44	2839/75	1.30	0,7
24x12x2	ePM10 50%	289x594x44	1700/75	0.78	0,4
20x20x2	ePM10 50%	495x495x44	2363/75	1.09	0,6
24x24x4	ePM10 50%	594x594x95	3400/68	2.47	1.50
24x20x4	ePM10 50%	492x594x95	2839/68	2.05	1.10
20x20x4	ePM10 50%	492x492x95	2363/68	1.70	1.00
24x12x4	ePM10 50%	289x594x95	1700/68	1.24	0.75