



## Advantages

- Moisture resistant frame board
- Radial Pleats
- Welded Steel Grid with Corrosion Inhibitor
- Diagonal Support
- Proprietary Dual High Lofted Fibers
- Built Strong

**Application:** Prevention of dust and dirt build up on heating/cooling coils within ventilation systems

**Type:** Pleated Panel

**Frame:** Water resistant cardboard

**Rec. final pressure drop acc. EN 13053:** 200 Pa

**Temperature max:** 70°C

**Mounting frames:** Front and side access housings and frames are available, Type 8, Type L, and FC Housings.

**Fire rating:** UL 900



Model Name	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Area (m <sup>2</sup> )	Weight (kg)
24x24x2	ePM10 50%	594x594x44	3400/75	1.56	0,8
24x20x2	ePM10 50%	495x597x44	2839/75	1.30	0,7
24x12x2	ePM10 50%	289x594x44	1700/75	0.78	0,4
20x20x2	ePM10 50%	495x495x44	2363/75	1.09	0,6
24x24x4	ePM10 50%	594x594x95	3400/68	2.47	1.50
24x20x4	ePM10 50%	492x594x95	2839/68	2.05	1.10
20x20x4	ePM10 50%	492x492x95	2363/68	1.70	1.00
24x12x4	ePM10 50%	289x594x95	1700/68	1.24	0.75