

Advantages

- Range of standard sizes
- Compact design
- Very high efficiency
- HI3 are individually tested

Application:Very high efficiency final filtration in air conditioning systems housings-ducts or diffusers

Type:Box Filter

Gasket:Polyurethane, endless foamed

Media:Glass fiber

Separator:Hot Melt

Max. final pressure drop:500

Temperature max:70°C

Mounting frames:Mounting systems: FCB Housings, Ducts, Diffusers, CAMSAFE

Fire rating: DIN 53438 Class F1



| Model Name | EN1822 | Dimensions WxHxD (mm) | Air Flow/pressure drop (m ³ /h/Pa) | Area (m ²) | Weight (kg) |
|-------------------------|--------|-----------------------|---|------------------------|-------------|
| CED13-575x575x150-P0-S | | 575x575x150 | 1161/250 | | 11 |
| CED13-305x610x150-P0-S | | 305x610x150 | 645/250 | | 6 |
| CED13-610x610x150-P0-S | | 610x610x150 | 1305/250 | | 12 |
| CED13-762x610x150-P0-S | | 762x610x150 | 1635/250 | | 13.5 |
| CED13-914x610x150-P0-S | | 914x610x150 | 1958/250 | | 15 |
| CED13-1219x610x150-P0-S | | 1219x610x150 | 2618/250 | | 18 |
| CEX13-305x305x150-P0 | | 305x305x150 | 380/250 | | 4 |
| CEX13-457x457x150-P0-S | | 457x457x150 | 867/250 | | 10 |
| CEX13-575x575x150-P0-S | | 575x575x150 | 1384/250 | | 11 |
| CEX13-305x610x150-P0-S | | 305x610x150 | 773/250 | | 6 |
| CEX13-610x610x150-P0-S | | 610x610x150 | 1565/250 | | 12 |
| CEX13-762x610x150-P0-S | | 762x610x150 | 1957/250 | | 13.5 |
| CEX13-914x610x150-P0-S | | 914x610x150 | 2348/250 | | 15 |
| CEX13-1219x610x150-P0-S | | 1219x610x150 | 3131/250 | | 18 |
| CEG13-305x610x292-P0-S | | 305x610x292 | 893/250 | | 7 |
| CEG13-457x610x292-P0-S | | 457x610x292 | 1340/250 | | 9.9 |
| CEG13-610x610x292-P0-S | | 610x610x292 | 1804/250 | | 12.5 |
| CEG13-762x610x292-P0-S | | 762x610x292 | 2251/250 | | 16 |
| CET13-305x610x292-P0-S | | 305x610x292 | 1230/250 | | 7 |
| CET13-457x610x292-P0-S | | 457x610x292 | 1850/250 | | 9.9 |
| CET13-610x610x292-P0-S | | 610x610x292 | 2485/250 | | 12.5 |

Absolute CE

| Model Name | EN1822 | Dimensions WxHxD (mm) | Air Flow/pressure drop (m ³ /h/Pa) | Area (m ²) | Weight (kg) |
|----------------------------|--------|--------------------------|--|---------------------------|----------------|
| CET13-762x610x292- P0-S | | 762x610x292 | 3100/250 | | 16 |

**Other sizes are available on request*